

Can JinkoSolar PV modules be installed in permanent shading conditions?

Operation in permanent shading conditions is not recommended. Do not install the PV module near open flame or flammable materials. JinkoSolar PV modules have passed the IEC 61701 salt spray corrosion test (test method 6). PV modules can be installed at a distance of 50m away from the seashore.

Where should Jinko Solar PV modules be installed?

.2.2 Site Selection In most applications, Jinko solar PV modules should be installed in a location where they will receive maximum sunlight throughout the year. In the Northern Hemisphere, the module should typically face south, and in the Southern Hemisphere, the modules should t

Do JinkoSolar PV modules pass the salt spray corrosion test?

JinkoSolar PV modules have passed the IEC 61701 salt spray corrosion test (test method 6). PV modules can be installed at a distance of 50m away from the seashore. In the case when the modules are installed within 50m to 500m distance from the seashore, the connectors shall be protected, i.e., adding dust plugs.

What should I not do if my Jinko Solar module Fires?

Do not use water to extinguish the fire when the power supply is not disconnected. Do not remove any part installed by Jinko Solar or disassemble the module. All instructions should be read and understood before attempting to install, wire, operate and maintain the module. Don't lift up PV modules using the attached cables or the junction box.

What pressure does a Jinko module meet?

er stickers match. Jinko modules are designed to meet a maximum positive (or downward) pressure of 3600Pa (Only refer to the mentioned module type in this manual) and negative (or upward) pressure of 1600Pa. This design load was then tested with a safety

How to Mount Jinko frameless dual glass modules?

Jinko Frameless Dual glass modules usually can be mounted by the clamps. Jinko Dual glass modules of frame usually can be mounted by the clamps and bolts. According to IEC61215 for a maximum positive design loading of below 3600Pa, and negative design loading 1600Pa, with 1.5 times safety factor.

Web: <https://www.gennergyps.co.za>